

NEW

Model 6110

DIGITAL RCD TESTER

FEATURES

- Microprocessor controlled for high reliability and accuracy
- Extra Large LCD screen for easy readability
- Accurate digital readout of disconnection time
- LED indicators to check correct wiring status
- Phase angle switch permits testing at 0° & 180°
- Measures voltage between line & earth before testing
- Frequency measurement indication
- Hand strap included for easy holding



CE

KOICO 6110 ELECTRICAL SPECIFICATIONS

Function	KOICO 6110
Rated Tripping Current	3mA, 5mA, 10mA, 15mA, 20mA, 30mA, 50mA, 100mA, 150mA, 250mA, 300mA, 500mA
Operating voltage (L-E) (50Hz or 60 Hz)	230 V AC
Phase angle setting	0° and 180° selectable
Wiring Correctness indicator	Yes (LED's)
Timer resolution	1ms (Max. Time = 2.999s)
Timer accuracy	±2ms
Current accuracy	±5% ±1mA
Voltmeter (L-E)	10Vac ~ 280Vac (50Hz or 60Hz)
Voltmeter accuracy	±2% ±1Vac
Voltmeter resolution	1Vac
Power source	1.5V (AA) × 6 (Alkaline battery)
Operating temperature	0°C ~ 40°C
Storage temperature	-10°C ~ 50°C
Applicable standards	EN 61010-1 CAT III 300V, EN 61326-1
Dimensions & Weight	221(L) × 110(W) × 57(D)mm, Approx. 695g
Accessories	Model No.AR 60 (Test Leads) Model No.AR120 (Hard Carrying case) Model No.AR61 (Hand Strap) Instruction manual Batteries (1.5V AA x 6)



BACKLIGHT DISPLAY



HAND STRAP



ACCESSORIES