

KOICO[®]
Japan

LIGHT METER WITH DETACHABLE/ ROTATABLE LIGHT SENSOR

Model 7402



FEATURES

Measures upto 199900lux or 19990
Foot Candles

Detachable & Rotatable Light Sensor
offering maximum flexibility in use.

Large LCD Display with backlight

Data Hold & Min/Max functions available.



KOICO 7402 ELECTRICAL SPECIFICATIONS

Parameter	KOICO 7402
Light Range	0.0 ~ 19990 fc ; 0.00 ~ 199900 lx (0.0 to 199.9/1999/19990/199990lx) (0.0 to 19.9/199.9/1999/19990fc) Automatic or manual selection of range)
Resolution	0.01 lx - 100lx 0.1 fc - 10fc
Accuracy	±3%rdg, ±5dpts (Calibrated to standard incandescent lamp 2856°K)
Light Detector	Si Photodiode
Over Range Display	"-OL-" display
Angle Deviation from cosine characteristics	10°+1% 30°+2% 60°+5% 80°+20%
Response Time	0.5 sec
Operation Temperature	0°C to 40°C, 0-80% RH
Storage Temperature	-10°C -50°C, 0-70% RH
Power Source	1.5V AA x 2
Dimension and Weight	(LxWxH) 169mm x 63mm x 37mm, 185g

INCLUDED ACCESSORIES

Model No. AR140 (carrying case),
User's Manual,
Battery (1.5V AA x 2)



The contents of this leaflet are subject to change without notice. KOICO is powered by Graffim Private Limited, Japan